

Струйник KARCHER 850 mm

Струйник KARCHER 850 mm може да се използва при всички професионални водоструйни и пароструйни машини, дължина на тръбата 850 mm. От неръждаема стомана с винтово съединение за ръчно завиване. Има ергономично оформени капачки на ръкохватките. Върти се на 360 градуса под налягане.

Подходящ за:

HD 10/15-4 Cage Food	HD 7/14 -4M Plus *EU	HDS 12/14-4 ST Gas LPG
HD 10/23-4 S Plus	HD 7/14 -4MX	HDS 12/18-4 S
HD 10/23-4 SX Plus	HD 7/15 G	HDS 12/18-4 SX
HD 10/25-4 Cage Plus	HD 7/16-4 ST	HDS 13/20 De Tr1
HD 10/25-4 S Plus	HD 7/16-4M Plus *EU	HDS 13/20-4 S
HD 10/25-4 SX Plus	HD 7/16-4MX *EU	HDS 13/20-4 SX
HD 13/12-4 ST	HD 7/17 M Plus*EU	HDS 17/20 De Tr1
HD 13/18-4 S Plus	HD 7/17 MX *EU	HDS 5/11 U
HD 13/18-4 SX Plus	HD 7/18 C Plus	HDS 5/11 UX
HD 16/15-4 Cage Plus	HD 7/18 CX Plus	HDS 5/15 U
HD 17/14-4S Plus	HD 715	HDS 5/15 UX
HD 17/14-4SX Plus	HD 728 B Cage	HDS 6/14 C
HD 20/15-4 Cage Plus	HD 8/18-4M Plus *EU	HDS 6/14 CX
HD 25/15-4 Cage Plus	HD 8/18-4MX *EU	HDS 7/16 C
HD 5/12 C Plus	HD 9/18-4 ST	HDS 7/16 CX
HD 5/12 CX Plus	HD 9/20-4 M Plus	HDS 8/18-4 C
HD 5/15 C Plus	HD 9/20-4 MX Plus	HDS 8/18-4 CX
HD 5/15 CX Plus	HD 9/23 De	HDS 9/14-4 ST
HD 5/15 CX Plus + FR Classic	HD 9/23 G	HDS 9/16-4 ST Gas
HD 6/13 C Plus	HDS 10/20-4 M	HDS 9/18-4 M
HD 6/13 C Plus + FR Classic	HDS 10/20-4 MX	HDS 9/18-4 MX
HD 6/13 CX Plus	HDS 1000 Be	HDS-E 8/16 -4 M 36 kW
HD 6/15 M Plus *EU	HDS 1000 De	HDS-E 8/16-4 M 12 kW
HD 6/15 MX *EU	HDS 11/18-4 S Basic	HDS-E 8/16-4 M 24 kW
HD 6/15 St *EU	HDS 12/14-4 ST	
HD 7/10 CXF	HDS 12/14-4 ST Gas	



Технически характеристики

Дължина, mm 850



https://dikarconsult.com/index.php?route=extension/module/pdf&product_id=22493